


CURRENT 0.8 Ampere  
VOLTAGE RANG 50 to 1000 Volts

B1 THRU B7

### Features

- Low profile space
- Ideal for automated placement
- Glass passivated chip junction
- Low forward voltage drop
- Low leakage current
- High forward surge capability
- High temperature soldering:  
260°C/10 seconds at terminals
- Component in accordance to  
RoHS 2002/95/1 and WEEE 2002/96/EC



### Mechanical Date

- **Case:** SOF2-4 Molded plastic over glass passivated chip
- **Terminals:** Solder plated, solderable per J-STD-002B and JESD22-B102D
- **Polarity:** Polarity symbols marked on body

### Major Ratings and Characteristics

$I_{F(AV)}$	0.5 A, 0.8 A
$V_{RRM}$	50V to 1000V
$I_{FSM}$	20 A
$I_R$	5.0 $\mu$ A
$V_F$	1.1 V
$T_j$ max.	150 °C

### Maximum Ratings & Thermal Characteristics (T<sub>A</sub> = 25 °C unless otherwise noted)

Items	Symbol	B1	B2	B3	B4	B5	B6	B7	UNIT
Maximum repetitive peak reverse voltage	$V_{RRM}$	50	100	200	400	600	800	1000	V
Maximum RMS voltage	$V_{RMS}$	35	70	140	280	420	560	700	V
Maximum DC blocking voltage	$V_{DC}$	50	100	200	400	600	800	1000	V
Maximum average forward rectified current at T <sub>A</sub> =30°C -on glass-epoxy P.C.B. <sup>(1)</sup> -on aluminum substrate <sup>(2)</sup>	$I_{F(AV)}$				0.5	0.8			A
Peak forward surge current 8.3 ms single half sine-wave superimposed on rated load (JEDEC Method)	$I_{FSM}$				20				A
Thermal resistance from junction to ambient per leg	$R_{\theta JA}^{(1)}$ $R_{\theta JA}^{(2)}$			100	80				°C/W
Thermal resistance from junction to lead per leg <sup>(1)</sup>	$R_{\theta JL}$			30					°C/W
Operating junction and storage temperature range	$T_j, T_{STG}$			-55 to +150					°C

Note 1: On glass epoxy P.C.B. mounted on 0.06×0.04" (1.5×1.1mm) pads

Note 2: On aluminum substrate P.C.B. with an area of 0.8×0.8" (20×20mm) mounted on 0.06×0.04" (1.5×1.1mm) solder pad

### Electrical Characteristics (T<sub>A</sub> = 25 °C unless otherwise noted)

Items	Test conditions	Symbol	Min	Type	Max	UNIT
Instantaneous forward voltage per leg	$I_F=0.4A^{(3)}$	$V_F$	-	0.96	1.10	V
Reverse current per leg	$V_R=V_{DC}$	$T_j=25^\circ C$ $T_j=125^\circ C$	$I_R$	-	5 100	$\mu$ A


Note 3: Pulse test:300μs pulse width, 1% duty cycle.

CURRENT 0.8 Ampere  
 VOLTAGE RANG 50 to 1000 Volts


B1 THRU B7

### Rating and Characteristic Curves ( $T_A=25^\circ\text{C}$ Unless otherwise noted )


**Fig.1 Forward Current Derating Curve**




**Fig.2 Maximum Non-Repetitive Peak Forward Surge Current**



**Fig.3 Typical Instantaneous Forward Characteristics**




**Fig.4 Typical Reverse Leakage Characteristics**



CURRENT 0.8 Ampere  
VOLTAGE RANG 50 to 1000 Volts


B1 THRU B7

**Package Outline**



Dimensions in millimeters and (inches)

**Soldering Pad**



Dimensions In millimeters and (inches)