

CURRENT 1.0 Ampere  
 VOLTAGE RANG 50 to 1000 to 1500 Volts


1A1 THRU 1A7 THRU 1A9

**FEATURES**

- Low coat construction
- Low forward voltage drop
- Low reverse leakage
- High forward surge current capability
- High temperature soldering guaranteed:  
 260 /10 secods/.375 (9.5mm)lead length at 5 lbs(2.3kg) tension

**MECHANICAL DATA**

- Case: Transfer molded plastic
- Epoxy: UL94V-O rate flame retardant
- Polarity: Color band denotes cathode end
- Lead: Plated axial lead, solderable per MIL-STD-202E method 208C
- Mounting position: Any
- Weight: 0.0070 ounce, 0.20 grams



Dimensions in inches and (millimeters)

**MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS**

- Ratings at 25°C ambient temperature unless otherwise specified
- Single Phase, half wave, 60Hz, resistive or inductive load
- For capacitive load derate current by 20%

	SYMBOLS	1A1	1A2	1A3	1A4	1A5	1A6	1A7	1A8	1A9	UNIT
Maximum Repetitive Peak Reverse Voltage	$V_{RRM}$	50	100	200	400	600	800	1000	1200	1500	Volts
Maximum RMS Voltage	$V_{RMS}$	35	70	140	280	420	560	700	840	1050	Volts
Maximum DC Blocking Voltage	$V_{DC}$	50	100	200	400	600	800	1000	1200	1500	Volts
Maximum Average Forward Rectified Current 0.375 (9.5mm) lead length at $T_A=25$	$I_{(AV)}$	1.0									Amps
Peak Forward Surge Current 8.3ms single half sine wave superimposed on rated load (JEDEC method)	$I_{FSM}$	25									Amps
Maximum Instantaneous Forward Voltage @ 1.0A	$V_F$	1.1									Volts
Maximum DC Reverse Current at Rated DC Blocking Voltage per element	$I_R$	$T_A = 25$									$\mu A$
		$T_A = 125$									
Maximum Full Load Reverse Current, full cycle average 0.375 (9.5mm)lead length at $T_L=75$	$I_{R(AV)}$	30									$\mu A$
Typical Junction Capacitance (Note 1)	$C_J$	40									pF
Typical Thermal Resistance (Note 2)	$R_{\theta JA}$	50									/W
Operating Junction Temperature Range	$T_J$	-55 to +150									
Storage Temperature Range	$T_{STG}$	-55 to +150									

**Notes:**

1. Measured at 1.0MHz and Applied Reverse Voltage of 4.0V DC.
2. Thermal Resistance from junction to Ambient at .375 (9.5mm)lead length, P.C.board mounted.

CURRENT 1.0 Ampere  
 VOLTAGE RANG 50 to 1000 to 1500 Volts

**1A1 THRU 1A7 THRU 1A9**

RATING AND CHARACTERISTIC CURVES 1A1 Thru 1A7 Thru 1A9

FIG.1-TYPICAL FORWARD CURRENT DERATING CURVE




FIG.2-MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT




FIG.3-TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG.4-TYPICAL REVERSE CHARACTERISTICS




FIG.4-TYPICAL JUNCTION CAPACITANCE

